

On a Parametric Spline function

F.A.Abd El-Salam

Department of Mathematics and Engineering Physics, Faculty of Engineering, Benha University,
Shoubra-Cairo, Egypt

Abstract : This paper is concerned with the development of non-polynomial spline function approximation method to obtain numerical solution of ordinary and partial differential equations. The parametric spline function which depends on a parameter $p < 0$, is discussed which reduced to the ordinary cubic spline [1] when the parameter $p = 0$.

The numerical method is tested by considering an example.

Keywords : Cubic spline function, Parametric spline function, finite difference method.

I. Introduction

We consider a mesh Δ with nodal points x_i on the interval $[a, b]$ such that $\Delta: a = x_0 < x_1 < \dots < x_N = b$, where $h = x_i - x_{i-1}, i = 1(1)N$. Assume we are given the values $\{y_i\}_{i=0}^N$ of the function $y(x)$, with $[a, b]$ as its domain of definition. A spline function of degree m with nodes at the points $x_i, i = 1, \dots, N$ is a function $s_\Delta(x)$ with the following properties :

- (i) $s_\Delta(x)$ is a polynomial of degree m in each subinterval $[x_i, x_{i+1}], i = 0, 1, 2, \dots, N - 1$.
- (ii) $s_\Delta(x)$ and its first $(m - 1)$ derivatives are continuous on $[a, b]$.

A cubic spline function $s_\Delta(x)$, of class $C^2[a, b]$ interpolating to a function $y(x)$ defined on $[a, b]$ is such that in each interval $[x_{i-1}, x_i]$, $s_\Delta(x)$ is a polynomial of degree at most three and the first and second derivatives of $s_\Delta(x)$ are continuous on $[a, b]$.

II. Parametric Spline Function.

Given an interval $[a, b]$ and a mesh points with knots $a = x_0 < x_1 < \dots < x_n = b$, with $h = x_i - x_{i-1}, i = 1, 2, \dots, N$. A function $s_i(x) \in C^2[a, b]$ which interpolates the function $y(x)$ at the knots x_i depends on the parameter $p < 0$ and reduces to a cubic spline function in the interval $[x_{i-1}, x_i]$ as $p = 0$ is termed a parametric spline function. The parametric spline function when $p > 0$ is discussed in [2]. If $s_i(x)$ is a parametric spline function in the interval $[x_{i-1}, x_i]$, then it satisfies the following differential equation:

$$s_i''(x) - p^2 s_i(x) = (M_{i-1} - p^2 y_{i-1}) \left(\frac{x_i - x}{h} \right) + (M_i - p^2 y_i) \left(\frac{x - x_{i-1}}{h} \right) \quad (1)$$

where $M_i = y''(x_i), s_i(x_i) = y(x_i)$ and p is a parameter and we denote to $y(x_i)$ by y_i ,

Solving the differential equation (1) on the interval $[x_{i-1}, x_i]$, subject to $s_i(x_i) = y_i$ and $s_{i-1}(x_{i-1}) = y_{i-1}$ we obtain:

$$s_i(x) = \frac{h^2}{k^2 \sinh k} \{M_i \sinh kz_{i-1} - M_{i-1} \sinh kz_i\} - \frac{h^2}{k^2} \{(M_i - w y_i) z_{i-1} - (M_{i-1} - w y_{i-1}) z_i\} \quad (2)$$

where $z_{i-1} = \left(\frac{x - x_{i-1}}{h} \right)$, $w = \frac{k^2}{h^2}$ and $k = ph$

The continuity of the first derivative of $s_i(x)$ at x_i in the form $s'(x_i) = s'_{i+1}(x_i)$ which gives

$$y_{i+1} - 2y_i + y_{i-1} = h^2 \{ \alpha M_{i+1} + 2\beta M_i + \alpha M_{i-1} \} \quad (3)$$

where

$$\alpha = k^{-2} (1 - k \operatorname{csch} k) \quad (4)$$

$$\beta = -k^{-2} (1 - k \operatorname{coth} k) \quad (5)$$

The consistency relation for (3) leads to equation $2\alpha + 2\beta = 1$. Which may also be expressed as $k/2 = \tan k/2$. This equation has a zero root and an infinite number of non-zero roots. The smallest positive being $k = 8.986818916$ and for $k/2 = \tan k/2 \neq 0$, $\alpha + \beta = 1/2$. For the cubic spline $\alpha = 1/6$, $\beta = 1/3$.

From equation (2) some spline relations are derived which useful in solving boundary value problems . differentiate (2) at x_i, x_{i+1} then

$$s'_i(x_i) = -h(\alpha M_{i+1} + \beta M_i) + \left(\frac{y_{i+1} - y_i}{h} \right) \quad (6)$$

$$s'_i(x_{i+1}) = h(\beta M_{i+1} + \alpha M_i) + \left(\frac{y_{i+1} - y_i}{h} \right) \quad (7)$$

$$s'_i(x_i) + s'_i(x_{i+1}) = h(\beta - \alpha)(M_{i+1} + M_i) + 2 \left(\frac{y_{i+1} - y_i}{h} \right) \quad (8)$$

$$s'_i(x_{i+1}) + s'_i(x_i) = h(\beta + \alpha)(M_{i+1} + M_i) \quad (9)$$

when $p = 0$ equation (1) take the form

$$s''_i(x) = (M_{i-1}) \left(\frac{x_i - x}{h} \right) + (M_i) \left(\frac{x - x_{i-1}}{h} \right) \quad (10)$$

which leads to the cubic spline function

$$s_i(x) = (M_{i-1}) \frac{(x_i - x)^3}{6h} + (M_i) \frac{(x - x_{i-1})^3}{h} + \left(y_{i-1} - \frac{h^2}{6} M_{i-1} \right) \frac{(x_i - x)}{h} + \left(y_i - \frac{h^2}{6} M_i \right) \frac{(x - x_{i-1})}{h} \quad (11)$$

$$x_{i-1} \leq x \leq x_i.$$

III. Application

(a) Numerical method for solving second-order differential equation.

Consider the second order differential equation

$$y'' = f(x, y), \quad a \leq x \leq b \quad (12)$$

$$y(a) = y_0 \quad (13)$$

$$y(b) = y_N \quad (14)$$

The difference equation (3) can be used to determine the approximate values of $y(x_i)$ at the knots points

$\{x_i\}, i = 1, 2, \dots, N$ where $N = \frac{b-a}{h}$. The difference equation when equivalent to (3) is given by

$$y_{i+1} - 2y_i + y_{i-1} = \frac{h^2}{k^2} \{ (1 - k \operatorname{csch} k) f_{i+1} - 2(1 - k \operatorname{coth} k) f_i + (1 - k \operatorname{csch} k) f_{i-1} \} \quad (15)$$

where $f_i = f(x_i, x_i)$

Equation (15) is explicit in y_{i+1} and its suitable for solving the differential equation (12)-(14).

(b) Numerical Example.

Consider the differential equation which describe the fluid flow inside a circular cylinder in the polar form

$$\nabla^2 \psi = 0$$

where
$$\nabla^2 \psi = \frac{\partial^2 \psi}{\partial r^2} + \frac{1}{r} \frac{\partial \psi}{\partial r} + \frac{1}{r^2} \frac{\partial^2 \psi}{\partial \theta^2}$$

with boundary conditions

$$\begin{aligned} \psi &= 0, && \text{on } r = 1 \\ \psi &= r \sin \theta && \text{as } r \rightarrow \infty \\ \psi &= 0 && \text{for } \theta = 0, \pi \end{aligned}$$

By using the transformation $r = e^t$ the problem transform to

$$\frac{\partial^2 \psi}{\partial t^2} + \frac{\partial^2 \psi}{\partial \theta^2} = 0 \tag{16}$$

with boundary conditions

$$\begin{aligned} \psi &= 0, && \text{on } t = 0 \\ \psi &= e^t \sin \theta && \text{as } r \rightarrow \infty \\ \psi &= 0 && \text{for } \theta = 0, \pi \end{aligned}$$

by considering the parametric spline function approximation in t -direction with step size $h = 0.2$ and mesh points $t_i = t_0 + ih, i = 1, 2, \dots, N$ In θ -direction we apply finite difference approach with step size $l = 0.1\pi$ with knots points $\theta_j = \theta_0 + jl, j = 1, 2, \dots, L$ and t_∞ is taken as 0.3. Equation (16) can be written in the form

$$M_{i,j} + \frac{\psi_{i,j+1} - 2\psi_{i,j} + \psi_{i,j-1}}{l^2} = 0$$

and by using equation (3) we have the system

$$\psi_{i,j} = \frac{1}{2} (\psi_{i+1,j} + \psi_{i-1,j}) - \frac{h^2}{2} \{ \alpha M_{i+1,j} + 2\beta M_{i,j} + \alpha M_{i-1,j} \}$$

$$M_{i,j} = - \frac{\psi_{i,j+1} - 2\psi_{i,j} + \psi_{i,j-1}}{l^2}$$

$$i = 1, 2, \dots, N-1, \quad j = 1, 2, \dots, L-1.$$

From the boundary conditions we have

$$M_{0,j} = 0,$$

$$M_{N,j} = \frac{1}{l^2} (\psi_{N,j+1} - 2\psi_{N,j} + \psi_{N,j-1}),$$

$$\psi_{0,j} = 0,$$

$$\psi_{N,j} = e^3 \sin \theta_j$$

The exact solution $\psi = 2 \sinh t \sin \theta$ we use Mathematica program to obtain the following numerical result with $N = 6, L = 10$. The computational results are present in the following table with the exact values between the brackets. This problem has earlier been discussed in [2].

	$t = 0.2$	$t = 0.4$	$t = 0.6$	$t = 0.8$	$t = 1.0$
$\theta = 0.1\pi$	0.125356 (0.124432)	0.255717 (0.253859)	0.39629 (0.393474)	0.552692 (0.54888)	0.731165 (0.726314)
$\theta = 0.2\pi$	0.23844 (0.236686)	0.486403 (0.485633)	0.753791 (0.748431)	1.5128 (1.4403)	1.39067 (1.38153)
$\theta = 0.3\pi$	0.328185 (0.325768)	0.669477 (0.664611)	1.0375 (1.03013)	1.44697 (1.43699)	1.91421 (1.90152)

$\theta = 0.4\pi$	0.385805 (0.382964)	0.787017 (0.781297)	1.21966 (1.21099)	1.70101 (1.68928)	2.25029 (2.23537)
$\theta = 0.5\pi$	0.405659 (0.402627)	0.827519 (0.821505)	1.28243 (1.27331)	1.78855 (1.77621)	2.3661 (2.3504)
$\theta = 0.6\pi$	0.385805 (0.382964)	0.787017 (0.781297)	1.21966 (1.21099)	1.70101 (1.68928)	2.25029 (2.23537)
$\theta = 0.7\pi$	0.328185 (0.325768)	0.669477 (0.664611)	1.0375 (1.03013)	1.44697 (1.43699)	1.91421 (1.90152)
$\theta = 0.8\pi$	0.23844 (0.236686)	0.486403 (0.485633)	0.753791 (0.748431)	1.5128 (1.4403)	1.39067 (1.38153)
$\theta = 0.9\pi$	0.125356 (0.124432)	0.255717 (0.253859)	0.39629 (0.393474)	0.552692 (0.54888)	0.731165 (0.726314)

References

- [1] J.Ahlberg, E.Nilson, J.Walsh, The Theory of Splines and Their Applications, Academic Press, New York (1967).
- [2] C.V.Raghavarao and S.T.P.T.Srinivas, Note on parametric spline function approximation, Computer Math. Appl. , 29(12),67-73 (1995).
- [3] C.V.Raghavarao , Y.V.S.S.Sanyasiraju and S.Suresh , A note on application of cubic splines to two point boundary value problems, Computers Math. Appl.,27(11),45-48(1994).
- [4] M.K.Jain and A.Tariq, Spline function approximation for differential equations, Comp.Math. in Appl. Mech. and Eng., 26,129-143(1981).