Study and Analysis of Public and Private Transport Accessibility

T. Srikanth¹, K.L.A.V.Harnadh¹

¹(Department of Civil Engineering, GMR Institute of Technology, India)

ABSTRACT : The Rural public transportation is insufficient, accessibility is very much required in countries like India for the movement of passenger and goods .to nearby towns with in aspects of public participation, for overall development. Rural areas are suffering from transport problems such as inadequate transport facilities in terms of shortage of buses and non-availability of services.

Present study focused to increase the public transport accessibility in safe and efficient way and also meeting future demand up to 2018 for study area.

Keywords – Accessibility, Public Transport, Questionnaires, Rural Regions and Surveys.

I. INTRODUCTION

Transportation has an important role to play in the conditions that affect global, national and regional economic entities. It is a strategic infrastructure that is so embedded in the socio-economic life of individuals, institutions and corporations that it is often invisible to the consumer, but always part of all economic and social functions. Transport routes are established to distribute resources between places where they are abundant and places where they are scarce, but only if the costs are lower than the benefits. Transportation studies are multidisciplinary that can involve engineering, behavioral, and economic aspects depending on the dimension being investigated such as operational management or planning. One of the current issues pertaining to rural traffic is the role of public transport. The recent studies says that the environmental quality of the roads and the lack of frequency of buses have brought the need for an efficient rural accessibility planning.

Rural Accessibility defines access needs of rural households in relation to the basic social and economic services a household requires with respect to mobility needs, it pays attention to: The purpose for which people travel, The availability of public transport services, The condition of the transport infrastructure, local level roads, footpaths, footbridges. This means by which people transport themselves and their goods, foot, bicycles, animals etc. The availability of social and economic services in relation to population density. Objective of this study is given below

- 1) The main objective is to study the public transportation accessibility and population percent of public and private transport in study area.
- 2) To study the existing trip generation and accessibility.
- 3) To analyze the future trip generation and accessibility required.

II. STUDY AREA

The area proposed for the study is within the Srikakulam (Dist.). The study area is between Rajam – Srikakulam (Dist.). It is located between latitudes and longitudes of (Rajam) 18.2800° N, 83.4000° E and (Srikakulam) 18.3000° N, 80.9000° E. The population of the study area is 7480 and people living in this area their major occupation is daily labor and farming. The small population and absence of major transport facilities made the Governments to pay little attention to the provision of public facilities in the area and particularly the development of modern transport network. As noted by accessibility levels are poor in zones.

III. DATA COLLECTION

Household survey questionnaire was designed to obtain information mainly about the trip details of the family members, the importance put on easy accessibility to different activity centers by the respondents and the satisfaction levels with the existing accessibility level.

The on-board survey was conducted to assess customer travel behavior. The surveyor will be asked customers to evaluate various elements of service as well as overall satisfaction, with the ultimate purpose of measuring the impact of the public transport on customer requirements compared to standard local bus service. Specific questions focused on customer behavior, including trip origins and destinations and frequency of public transport use.

www.iosrjournals.org

The villagers were asked to express their opinion in the form of satisfaction levels with the accessibility to various activities. The interview was conducted on one village at a time. At least one person from the research team was always present to guide the interviewers in case of any doubts and difficulties. At the end of a day, the data collected by different persons were checked. In case of some abnormal responses, the concerned interviewers were sent back the next day to verify.

IV. SAMPLE SIZE AND CONDUCT OF THE SURVEY

The zones located for sample collection in the main route i.e. Rajam - Srikakulam (Dist.) corridor. For this study, a field work was carried out and household & onboard based surveys were conducted in the area along the route. For collecting the data, 7 enumerators were hired. After having them well trained, a pilot survey was conducted to study how people would respond to the questionnaire so that adjustments or change in the questionnaire is done, then the main survey was conducted.

For household survey sample size is taken as 435 for each and every village, for onboard survey sample size was taken as 200 for each zone, based on the sample questionnaires were distributed to the respondents and the details are shown in table 4.1.

Name of the Village	Population	Number of households	Number of households interviewed
Rajam	850	322	170
Antakapalli	252	110	22
Pogiri	485	307	62
Palakandyam	343	211	43
Santa Uriti	240	105	21
Anandapuram	235	95	19
Ponduru	647	412	83
Rapaka	657	462	93
Reddipeta	826	316	63
Lolugu	673	286	53
Chilakapalem	783	530	106
Echerla	542	218	44
Srikakulam	947	498	100

Table 4.1: Village wise data collection as per bureau of public roads

V.I Trip Purpose

TRIP CHARACTERSTICS

From the total trips was collected as a part of the travel characteristics of the users and this was segregated based on work trip, academic, shopping and entertainment etc. The trip purpose composition is as shown in Figure 5.1. Among all the trips office and college trips are more.




Figure 5.1: Purpose of Trips

V.

V.II Trip Length

The trip lengths are collected from the onboard survey, the data obtained was presented in Figure 5. 2. Among all trip lengths, it has been observed that more than 30 km trip lengths were high in number and less than 5 km trip lengths are low in number.




Figure 5.2: Length of the Trip

V.III Income Ranges

The income of each group is categorized from the stated preference survey and the Figure 5.3 below indicates the income ranges of each individual group, 49% of the income group in the range between 10 to 15 thousand Indian rupees.




Figure 5.3: Ranges of Income

VI. DETERMINING THE LEVELS OF ACCESSIBILITY

Accessibility is interpreted at the local scale and at a personal level in terms of people's ability to gain access to certain facilities relative to the ability of the prevailing transport system to overcome the distance barriers involved. In order to determine the weights of different activities the data collected through the household interview survey and onboard survey was utilized. By taking the sample size from each zone and they are divided by the total number of the questionnaires while doing the survey, from that we get the weightage of activities. This analysis was carried out village-wise. It has already been mentioned that the respondents were asked to rate each activity.

Based on the weights and present accessibility to different activities obtained as shown in Table 6.1, the levels of accessibility are calculated for the 13 villages in the study area using equation . The results obtained are shown below

Overall accessibility levels are calculated by using the following equation

$$OAL = \sum_{i=1}^{n} w_i v_i$$

International Conference on Innovations in Civil Engineering SCMS School of Engineering and Technology

IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE) e-ISSN: 2278-1684, p-ISSN: 2320-334X PP 01-06

www.iosrjournals.org

Where: N = Number of basic activities required by individuals in the study area as obtained by interviewing. W_i = importance (weight) associated with the accessibility to the ith activity.

 V_i = present level of accessibility to the ith activity

Table 6.1: Total trips of each activities			
Activities	Total No of Trips		
Office	593		
Work	682		
College	557		
Entertainment	395		
Others	373		

After taking the sample size and separating trips from each and every village the weightage for each every activity is calculated by dividing the total trip by 2600(sample size)they are given below

 W_i = Weightage for the each activities are taken as

(Office = 0.22, College = 0.26, Work = 0.21, Entertainment = 0.15 and Others =0.14) Based on the ranges accessibility levels are determined they are given below.

Table 6.2: OAL ranges			
Level	Range		
Good	50		
Moderate	45		
Poor	40		

After determining the OAL in the study area the following areas are having poor accessibility levels, comparing to the remaining areas.

	Table 6.3: OAL			
Palakandyam	Santa Uriti	Reddipeta	Lolugu	Echrla
41.7	38.2	41.6	39	38.3

VII. MEASURES TO INCREASE THE ACCESSIBILITY LEVELS

- a) It has already been shown (Table 6.3) that the overall accessibility levels of all the villages in the study area are poor. The methodology developed in this study helps to suggest the measures to be taken to increase the overall accessibility of a selected village or the study area as a whole.
- It would be appropriate if the activities are considered one by one in descending order of their weights. b) The impact on overall accessibility level will be the highest with a unit increase in accessibility level to the activity with highest weight.
- c) In this study the accessibility to college has been given the highest weight with a value of 0.26 by the respondents. However, the accessibility levels with existing levels have been found to be poor Santa Uriti, Reddipeta and Lolugu respectively.
- d) One way to increase these values is to provide better accessibility to work and office activities, which can be achieved by providing a few more buses and bus stops in the villages or by providing better transport facilities to the existing points. Better transport facilities may be provided by better roads and provision of motorized or non-motorized vehicles.
- In this way, it is possible to identify the necessities in the villages against all the activities. Since the e) weights and overall accessibility levels are expressed numerically, the methodology helps the policy and decision makers to numerically calculate the improvement in the study area.

TRAVEL DEMAND MODELING VIII.

Travel demand modeling aims to establish the spatial distribution of travel by zones. This model implies a procedure for predicting what travel decisions people would like to make given the generalized travel cost of each alternatives. The base decisions include the choice of destination, the choice of the mode.

VIII.I Frater's Growth Factor model

According to this method, the total trips for each zone are distributed to different activities, according to relative attractiveness of each movement. Thus, the future trips estimated for any zone would be distributed to the movements involving that zone in proportion to the existing trips between it and each other zone.

VIII.II Assessment of Growth Factor

The assessment of growth factor is taken from the growth of population, here we are taken 5 years for future trip generation and the value is 4.9.% is the maximum growth in the past five years and in proportion to the expected growth of each other zone. it is calculated by using equation.

$$T_{i:J} = t_{i-j} x \frac{P_i}{p_i} x \frac{A_j}{a_j} x \frac{\sum_{i=0}^k t_{i-k}}{\sum_{i=0}^k \left[\frac{A_k}{a_k}\right] x t_{i-k}}$$

Where:	T _{i-j}	=	Future trips from zone i to zone j
	t _{i-i}	=	Present trips from zone i to zone j
	P _i	=	Future trips produced at zone i
	p _i	=	Present trips attracted at zone i

 $A_i =$ Future trips attracted to zone j

 $A_i = Future trips attracted to zone J$

 $a_j = Present trips attracted to j$

k = Total numbers of zone

Table 8.1: Future Trips						
Palakandyam	Santa Uriti	Reddipeta	Lolugu	Echerla		
1042.3	1079.8	3551.7	3391.5	6430.5		

IX. CONCLUSION

This work quantified the travel characteristics of people and identified the choice of mode of commuters in Rajam – Srikakulam (Dist.). The data is collected by means of a household survey and onboard survey along the study area, which provided the information about their economic status and travel behavior of a sample population.

The study showed that the accessibility to basic needs in the study area is highly inadequate.

- 1. The average household size was 6 and trip length were observed as 20 km from their origin to destination points from each village and the respondents in Santa Uriti, Ponduru, Rapaka, lologu indicated higher importance ratings on accessibility to work, educational facilities office in the study.
- 2. In the study area, villages having the problems with lack of frequency and time maintenance comparing to the other areas. And the villages, palakandyam(41.7) Santa uriti (38.2), Lolugu (39), Reddipeta(41.6) and Echerla (38.3) are having low accessibility levels comparing to the ranges given in table 5.1.3.
- 3. The future trip generation with growth factor method shown maximum increase comparing with the present trips, highest is lolugu 11.4 times comparing to the other areas here the trip generation is very high

References

Journal Papers:

- [1] C. V. Phani Kumar, Debasis Basu, and Bhargab Maitra. Modeling Generalized Cost of Travel for Rural Bus Users: A Case Study, *Journal of Public Transportation*, *Vol. 7, No. 2*, 2004, PP: 59 72.
- [2] Danang parikesit and La Ode Muhammad magribi, Development of a dynamic model for investigating the Interaction between rural transport and development, *Journal of the Eastern Asia Society for Transportation Studies*. Vol. 6, 2005, PP: 2747 2761.
- [3] Mairead Cantwell, Brian Caulfield, Margaret O'Mahony, Examining the Factors that Impact Public Transport Commuting Satisfaction, *Journal of Public Transportation*, Vol. 12, No. 2, 2009, PP :1 - 21.
- [4] Ar Anuj Jaiswal, Ashutosh Sharma, Jigyasa Bisaria, Estimation of Public Transport Demand in Million Plus Indian Cities based on Travel Behavior, ISSN: 2249 – 8958, Volume-2, Issue-1, 2012, PP :249 - 259.
- [5] Amiruddin Ismail, Mohammad Ganji, Mohammad Hesam Hafezi, Foad Shokri and Riza Atiq, An Analysis of Travel Time in Multimodal Public Transport, *Australian Journal of Basic and Applied Sciences, ISSN 1991-8178*, 2012, PP: 165-172.
- [6] Mir Aftab Hussain Talpur, Madzlan Napiah, Imtiaz Ahmed Chandio & Shabir Hussain Khahro, Transportation Planning Survey Methodologies for the Proposed Study of Physical and Socio-economic Development of

International Conference on Innovations in Civil Engineering SCMS School of Engineering and Technology

IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE) e-ISSN: 2278-1684, p-ISSN: 2320-334X PP 01-06

www.iosrjournals.org

Deprived Rural Regions, Canadian Center of Science and Education, Modern Applied Science. 6, No. 7, ISSN 1913-1852, 2012, PP :1 - 16.

Theses:

- [7] Prof. Ashoke K. Sarkar and M.A. M Mashiri, *Quantification of accessibility levels of rural areas: A case study in the northern province South Africa*, Transportek, Council of Scientific and Industrial Research, 1995, PP : 1 44.
- [8] Grace Corpuz, Public Transport or Private Vehicle: Factors That Impact on Mode Choice, 30th Australasian Transport Research Forum, 2006, PP: 1 11.
- [9] J. Aderamo and S. A. Magaji Rural Transportation and the Distribution of Public Facilities in Nigeria: A Case of Edu Local Government Area of Kwara State, *Department of Geography, University of Ilorin, Ilorin, Nigeria* 2010, PP: 171-179.
- [10] Marie Thynell, Dinesh Mohan, Geetam Tiwari, Sustainable transport and the modernisation of urban transport in Delhi and Stockholm Transportation Research and Injury Prevention Programme, *Indian Institute of Technology*, *Delhi*, *India*, 2010, PP: 421-429.